

# **Material Safety Data Sheet**

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:**3M(TM) Marine Silicone Sealant - White, P.N. 08017, 08027**MANUFACTURER:**3M**DIVISION:**Industrial Adhesives and Tapes Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000

### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

<b>Issue Date:</b>	03/26/12
Supercedes Date:	05/09/07

Document Group: 07-7756-5

### **Product Use:**

Specific Use: Intended Use: Marine Mildew Resistant Silicone Sealant

# **SECTION 2: INGREDIENTS**

#### <u>Ingredient</u>

Siloxanes And Silicones, DI-ME, Hydroxy-Terminated Silica Ethyltriacetoxysilane Methyltriacetoxysilane Poly(Dimethylsiloxane) Titanium Dioxide

<u>% by Wt</u>

<u>C.A.S. No.</u>

# **SECTION 3: HAZARDS IDENTIFICATION**

## **3.1 EMERGENCY OVERVIEW**

Specific Physical Form: Paste
Odor, Color, Grade: white paste, acetic acid odor
General Physical Form: Solid
Immediate health, physical, and environmental hazards: May cause severe eye irritation. May cause severe skin irritation.

# **3.2 POTENTIAL HEALTH EFFECTS**

#### **Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Skin Contact:**

Severe Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention. **Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

Autoignition temperature	
Flash Point	
Flammable Limits(LEL)	
Flammable Limits(UEL)	

No Data Available Not Applicable Not Applicable Not Applicable

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

### **6.2.** Environmental precautions

Collect the resulting residue containing solution. Dispose of collected material as soon as possible.

### **Clean-up methods**

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

## 7.1 HANDLING

Avoid eye contact with vapors, mists, or spray. Avoid skin contact. Avoid breathing of vapors, mists or spray. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Do not ingest. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid contact with oxidizing agents.

## 7.2 STORAGE

Store away from oxidizing agents.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment. Use with appropriate local exhaust ventilation. Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device.

# 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

### 8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. Gloves made from the following material(s) are recommended: Butyl Rubber Neoprene Polymer laminate

#### 8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half facepiece air-purifying respirator with acid gas cartridges

. Select and use respiratory protection to prevent an inhalation exposure based on the results of an exposure assessment. Consult with your respirator manufacturer for selection of appropriate types of respirators.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## **8.3 EXPOSURE GUIDELINES**

<u>Ingredient</u>	<u>Authority</u>	<b>Type</b>	<u>Limit</u>	Additional Information
Silica	CMRG	TWA, as respirable	3 mg/m3	
		dust		
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of	
			particles/cu. ft.	
Titanium Dioxide	ACGIH	TWA	10 mg/m3	
Titanium Dioxide	CMRG	TWA, as respirable	5 mg/m3	
		dust		
Titanium Dioxide	OSHA	TWA, as total dust	15 mg/m3	

### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form:
Odor, Color, Grade:
General Physical Form:
Autoignition temperature
Flash Point
Flammable Limits(LEL)
Flammable Limits(UEL)
Boiling Point
Density
Vapor Density
Von on Duogenne

Vapor Pressure

Specific Gravity pH Melting point Solubility In Water

Evaporation rate Hazardous Air Pollutants Volatile Organic Compounds Paste white paste, acetic acid odor Solid No Data Available Not Applicable Not Applicable Not Applicable 1.02 g/cm3 Not Applicable

Not Applicable

1.02 [*Ref Std:* WATER=1] *Not Applicable No Data Available No Data Available* 

Not Applicable 0 % weight [*Test Method:* Calculated] 35 g/l [*Test Method:* tested per EPA method 24] [*Details:* low solid less exempts]

Kow - Oct/Water partition coef Percent volatile VOC Less H2O & Exempt Solvents VOC Less H2O & Exempt Solvents Viscosity No Data Available 2 - 4 % weight 35 g/l [*Test Method:* tested per EPA method 24] 3.4 % [*Test Method:* tested per EPA method 24] Not Applicable

# SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: 10.1 Conditions to avoid Not determined

**10.2 Materials to avoid** Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

## Hazardous Decomposition or By-Products

<u>Substance</u>	<b>Condition</b>
Acetic Acid	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion
Oxides of Sulfur	During Combustion

Hazardous Decomposition: Product releases acetic acid during cure.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

## ECOTOXICOLOGICAL INFORMATION

Not determined.

# CHEMICAL FATE INFORMATION

Not determined.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

### EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

# **SECTION 14:TRANSPORT INFORMATION**

### For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: REGULATORY INFORMATION**

## **US FEDERAL REGULATIONS**

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## STATE REGULATIONS

Contact 3M for more information.

## **CHEMICAL INVENTORIES**

Contact 3M for more information.

## **INTERNATIONAL REGULATIONS**

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

### NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Reason for Reissue:** The MSDS has been revised because 3M has adopted the 16-section ANSI/ISO format. The potential hazards of the product have not changed. We encourage you to reread the MSDS and review the information.

**Revision Changes:** 

Section 1: Product use information was modified.

Section 1: Division name was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 3: Potential effects from eye contact was modified.

Section 3: Potential effects from skin contact information was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Section 8: Skin protection - recommended gloves information was modified.

Section 8: Respiratory protection - recommended respirators information was modified.

Section 4: First aid for ingestion (swallowing) - decontamination - was modified.

Section 14: Transportation legal text was modified.

Section 15: Inventories information was modified. Section 9: Vapor density value was modified. Section 9: Vapor pressure value was modified. Section 9: Boiling point information was modified. Section 5: Flammable limits (UE) information was modified. Section 5: Flammable limits (LEL) information was modified. Section 5: Autoignition temperature information was modified. Section 5: Flash point information was modified. Section 9: Property description for optional properties was modified. Section 9: Specific gravity information was modified. Section 9: pH information was modified. Section 9: Melting point information was modified. Section 9: Solubility in water value was modified. Section 8: Respiratory protection - recommended respirators guide was modified. Section 9: Flash point information was modified. Section 9: Flammable limits (LEL) information was modified. Section 9: Flammable limits (UEL) information was modified. Section 9: Autoignition temperature information was modified. Section 3: Immediate skin hazard(s) was added. Section 3: Immediate eye hazard(s) was added. Section 9: Density information was added. Section 2: Ingredient table was added. Section 8: Exposure guidelines ingredient information was added. Section 8: Exposure guidelines data source legend was added. Section 6: 6.2. Environmental precautions heading was added. Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added. Section 10.1 Conditions to avoid heading was added. Section 10.2 Materials to avoid heading was added. Section 16: Web address was added. Section 6: Environmental procedures information was added. Section 6: Methods for cleaning up information was added. Section 10: Materials to avoid physical property was added. Section 10: Conditions to avoid physical property was added. Section 1: Address was added. Copyright was added. Company logo was added. Section 6: Clean-up methods heading was added. Telephone header was added. Company Telephone was added. Section 1: Emergency phone information was added. Section 1: Emergency phone information was deleted. Company Logo was deleted. Copyright was deleted. Section 16: Web address heading was deleted. Section 6: Release measures information was deleted. Section 6: Release measures heading was deleted. Section 10: Materials and conditions to avoid physical property was deleted.

Section 1: Address line 1 was deleted.

Section 1: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a

particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

### 3M USA MSDSs are available at www.3M.com