

# **Material Safety Data Sheet**

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) Scotch-Weld(TM) Hot Melt Adhesive High Tack PSA 3794

**MANUFACTURER:** 3M

**DIVISION:** Industrial Adhesives and Tapes

**ADDRESS:** 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 04/27/2006 **Supercedes Date:** 11/22/2002

**Document Group:** 09-4285-4

**Product Use:** 

Specific Use: Pressure Sensitive Hot-melt adhesive

# **SECTION 2: INGREDIENTS**

Ingredient C.A.S. No. % by Wt

SYNTHETIC RUBBER BASED ADHESIVE N.J. TRADE SECRET REGISTRY Trade Secret NO. 390279330-5001

## **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Solid Block or Slab **Odor, Color, Grade:** tan, slight resinous odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause thermal burns.

## 3.2 POTENTIAL HEALTH EFFECTS

### **Eye Contact:**

Vapors from heated material may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### 3M MATERIAL SAFETY DATA SHEET 3M(TM) Scotch-Weld(TM) Hot Melt Adhesive High Tack PSA 3794 04/27/2006

Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

## **Skin Contact:**

Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

#### **Inhalation:**

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

## **Ingestion:**

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

**Skin Contact:** Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Flash Point >=400 °F [Test Method: Cleveland Open Cup]

#### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus

Page 2 of 7

(SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Reclaim undamaged product. Collect as much of the spilled material as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

## 7.1 HANDLING

Avoid skin contact with hot material. Avoid eye contact with vapors, mists, or spray. Keep out of the reach of children.

## 7.2 STORAGE

Store away from heat.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Not applicable. Use in a well-ventilated area.

## **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

## 8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

#### 8.2.2 Skin Protection

Wear appropriate gloves, such as Nomex, when handling this material to prevent thermal burns. Avoid skin contact with hot material.

#### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

## 8.2.4 Prevention of Swallowing

Do not ingest.

## 8.3 EXPOSURE GUIDELINES

None Established

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form:

Odor, Color, Grade:

Solid Block or Slab
tan, slight resinous odor

General Physical Form: Solid

Flash Point >=400 °F [Test Method: Cleveland Open Cup]

**Boiling point Not Applicable Density**0.94 g/cm3

Vapor Pressure Nil

Specific Gravity .94 [Ref Std: WATER=1]

pH Not Applicable

Melting point 224 °F

Solubility in Water Nil

Evaporation rateNot ApplicableHazardous Air Pollutants00 % weightVolatile Organic Compounds<=1 g/l</td>Percent volatile00 % weightPercent volatileNegligibleVOC Less H2O & Exempt Solvents<=1 g/l</td>

Viscosity Approximately 8100 centipoise [Details: CONDITIONS: @350 F.]

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

**Substance** Condition

HydrocarbonsDuring CombustionCarbon monoxideDuring CombustionCarbon dioxideDuring Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

## ECOTOXICOLOGICAL INFORMATION

Not determined.

## CHEMICAL FATE INFORMATION

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Reclaim if feasible. If product can't be reclaimed, dispose of waste product in a sanitary landfill. Alternatively, incinerate the waste product in an industrial, commercial, or municipal incinerator. As a disposal alternative, incinerate in an industrial or commercial facility.

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

#### **ID** Number(s):

62-3794-6630-3, 62-3794-6636-0

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

## **SECTION 15: REGULATORY INFORMATION**

## US FEDERAL REGULATIONS

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## STATE REGULATIONS

Contact 3M for more information.

## **CHEMICAL INVENTORIES**

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **Revision Changes:**

Section 1: Product name was modified.

Section 16: NFPA hazard classification heading was modified.

Section 16: NFPA hazard classification for health was modified.

Section 1: Division name was modified.

Copyright was modified.

Section 5: Fire fighting procedures information was modified.

Section 6: Release measures information was modified.

Section 7: Handling information was modified.

Section 8: Engineering controls information was modified.

Section 8: Eye/face protection phrase was modified.

Section 8: Skin protection phrase was modified.

Section 13: Waste disposal method information was modified.

Section 15: 311/312 hazard categories heading was modified.

Section 15: International regulations information was modified.

Section 15: State regulations information was modified.

Section 15: US federal regulations information was modified.

Section 4: First aid for inhalation - termination of exposure - was modified.

Section 4: First aid for inhalation - medical assistance - was modified.

Section 10: Hazardous polymerization heading was modified.

Section 14: Transportation legal text was modified.

Section 16: NFPA explanation was modified.

Page Heading: Product name was modified.

#### 3M MATERIAL SAFETY DATA SHEET 3M(TM) Scotch-Weld(TM) Hot Melt Adhesive High Tack PSA 3794 04/27/2006

- Section 15: Inventories information was modified.
- Section 12: Ecotoxicological information heading was modified.
- Section 12: Chemical fate information heading was modified.
- Section 16: NFPA hazard classification for special hazards was modified.
- Section 8: Exposure guidelines information none was modified.
- Section 12: Ecotoxicological phrase was modified.
- Section 12: Chemical Fate phrase was modified.
- Section 2: Ingredient phrase was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

Page 7 of 7