



Revision Number: 003.1 Issue date: 04/02/2010

# PRODUCT AND COMPANY IDENTIFICATION

246 Threadlocker Medium Strength Product name:

Product type: Anaerobic Sealant IDH number: 196508 Item number: 29513 **United States** Region:

Company address: **Contact information:** Henkel Corporation Telephone: 860.571.5100

Emergency telephone: 860.571.5100

Internet: www.henkelna.com

# 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

HEALTH: Physical state: Liquid \*2 Color: Opaque, Blue FLAMMABILITY: 1 PHYSICAL HAZARD: Odor: Mild 1

**Personal Protection:** See MSDS Section 8

CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. WARNING:

MAY CAUSE ALLERGIC SKIN REACTION.

MAY BE HARMFUL IF SWALLOWED OR INHALED.

Relevant routes of exposure: Skin, Lungs, Eyes

**Potential Health Effects** 

One Henkel Way

Rocky Hill, Connecticut 06067

Inhalation: May cause respiratory tract irritation.

May cause skin irritation with discomfort or rash. Causes skin irritation. May cause allergic skin Skin contact:

reaction.

Eye contact: Contact with eyes will cause irritation.

Ingestion: May be harmful if swallowed.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

# **COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous components	CAS NUMBER	%
Silsesquioxanes, 3-[(2-methyl-1-oxo-2-propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	193486-90-7	30 - 60
Hexanedioic acid, polymer with 1,4-butanediol and 1,2-propanediol, dodecanoate	68186-73-2	10 - 30
Hydroxyalkyl methacrylate	27813-02-1	5 - 10
Maleimide resin	3006-93-7	5 - 10
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	24448-20-2	1 - 5
Silica, amorphous, treated	68909-20-6	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
Saccharin	81-07-2	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1

IDH number: 196508 Product name: 246 Threadlocker Medium Strength

# 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: If symptoms develop and persist, get medical attention. Wash clothing before

reuse. Remove contaminated clothing and footwear. Wash with soap and

water.

**Eye contact:** Get medical attention. Flush with copious amounts of water, preferably,

lukewarm water for at least 15 minutes, holding eyelids open all the time.

**Ingestion:** Keep individual calm. Do not induce vomiting. Get medical attention.

#### 5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Formaldehyde. Irritating organic vapours. Oxides of nitrogen. Oxides of

carbon.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Store in a partly filled, closed container until disposal. Soak up with inert

absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

# 7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	None	None	None	None
Hexanedioic acid, polymer with 1,4-butanediol and 1,2-propanediol, dodecanoate	None	None	None	None
Hydroxyalkyl methacrylate	None	None	None	1 ppm TWA 3 ppm STEL
Maleimide resin	None	None	None	None
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	None	None	None	None
Silica, amorphous, treated	10 mg/m3 TWA Inhalable dust.	6 mg/m3 TWA	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Saccharin	None	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None None	

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

**Skin protection:** Natural rubber gloves. Use impermeable gloves and protective clothing as

necessary to prevent skin contact. Neoprene gloves. Butyl rubber gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Opaque, Blue Odor: Mild

Odor threshold: Not available pH: Not applicable

Vapor pressure:< 5 mm hg (80 °F (26.7 °C))Boiling point/range:< 300 °F (> 148.9 °C)

Melting point/ range:Not availableSpecific gravity:1.147Vapor density:Not available

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available

Slight

Not available

2.11 %; 22 g/l

# 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: Irritating organic vapours. Oxides of carbon. Oxides of nitrogen.

Formaldehyde.

**Incompatible materials:** Free radical initiators. Reducing agents. Strong alkalis. Amines. Peroxides.

Azo-compounds. Strong acids and oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

# 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 10,000 mg/kg

Acute dermal product toxicity: LD50 (rabbit) > 5,000 mg/kg

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	No	No	No
Hexanedioic acid, polymer with 1,4- butanediol and 1,2-propanediol, dodecanoate	No	No	No
Hydroxyalkyl methacrylate	No	No	No
Maleimide resin	No	No	No
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	No	No	No
Silica, amorphous, treated	No	No	No
Cumene hydroperoxide	No	No	No
Saccharin	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

Hazardous components	Health Effects/Target Organs
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	Allergen, Irritant
Hexanedioic acid, polymer with 1,4-butanediol and 1,2- propanediol, dodecanoate	No Records
Hydroxyalkyl methacrylate	Irritant, Allergen
Maleimide resin	No Target Organs
2-Propenoic acid, 2-methyl-, (1-methylethylidene)	Irritant, Allergen
Silica, amorphous, treated	No Target Organs
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Saccharin	No Target Organs
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

# 14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

#### **U.S. Department of Transportation Ground (49 CFR)**

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None
None

IDH number: 196508 Product name: 246 Threadlocker Medium Strength

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
None
Packing group:
None

# 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Delayed Health, Immediate Health

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 196508

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

WHMIS hazard class: D.2.B

# 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.