Material Safety Data Sheet



Henkel

Revision Number: 001.1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type: ViperLube(TM) Lubricant

Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067 IDH number: 457453 Item number: 36780 Region: United States Contact information: Telephone: 860.571.5100 Emergency telephone: 860.571.5100 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

		EMERGENCY O	<u>VERVIEW</u> HMIS:	
Physical state: Color: Odor:	Semi-Solid White Mild, Petrol	eum	HEALTH: FLAMMABILITY: PHYSICAL HAZARD: Personal Protection:	1 1 0 See MSDS Section 8
CAUTION:	MA	Y CAUSE EYE AND	SKIN IRRITATION.	
Relevant routes of exp	osure:	Skin, Inhalation, Eyes		
Potential Health Effects	<u>8</u>			
Inhalation: Skin conta Eye contac Ingestion:	ct:	May cause irritation due t Non-irritating.	respiratory tract irritation and delay o defatting of the skin. trointestinal irritation, nausea, vomit	
Existing conditions age exposure:	gravated by	Eye, skin, and respiratory	v disorders.	
		This material is considere 1910.1200).	ed hazardous by the OSHA Hazard	Communication Standard (29 CFI

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%	
Polyalphaolefins	Proprietary	30 - 60	
Zinc oxide	1314-13-2	5 - 10	
Calcium carbonate	471-34-1	5 - 10	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	5 - 10	

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.	
Skin contact:	If high pressure forces the product under the skin get immediate medical attention. Wash with soap and water. If hot material contacts the skin, immediately cool before attempting removal. If symptoms develop and persist, get medical attention.	
Eye contact:	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.	

Ingestion:

Get medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person. Aspiration may cause pulmonary edema and pneumonitis.

5. FIRE FIGHTING MEASURES				
Flash point:	> 180 °C (> 356°F)			
Autoignition temperature:	Not determined			
Flammable/Explosive limits - lower:	Not available			
Flammable/Explosive limits - upper:	Not available			
Extinguishing media:	Foam. Water fog. Small Fires: Dry chemical. Sand. Large fires: Treat as oil fire. Vermiculite.			
Special firefighting procedures:	Water spray may be ineffective. Oil will float on water and can spread fire.			
Unusual fire or explosion hazards:	None			
Hazardous combustion products:	Oxides of sulfur. Oxides of carbon.			
6. ACCIDEN	6. ACCIDENTAL RELEASE MEASURES			

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not allow product to enter sewer or waterways.
Clean-up methods:	Clean-up methods - large spillage. Flush with water. Follow all local, state, federal and provincial regulations for disposal.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed.

Storage:

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

Keep in a cool, well ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None
2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction.	5 mg/m3 TWA Fume. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
5 mg/m3 TWA Mist. 10 mg/m3 STEL Mist.	500 ppm (2,000 mg/m3) TWA	None	None
when general v	ventilation is not sufficie	ocal exhaust ventilation ent to control airborne	on is recommended contamination
ventilation, wea	ar a properly fitted orga	nic vapor/particulate	respirator approved
Safety glasses with side-shields. Goggles.			
Cover as much	n of the exposed skin a	rea as possible with a	appropriate clothing.
CAL AND CHEM	ICAL PROPERT	IES	
Not available Not available < 0.01 mm hg Not available Not available 0.95 - 1.05 at 2 Not available > 180 °C (> 35 Not available	(68 °F (20°C)) 25 °C (77°F)		
	5 mg/m3 TWA mist 10 mg/m3 STEL mist 2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction. 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Mist. 10 mg/m3 STEL Mist. 10 mg/m3 STEL Mist. 10 mg/m3 STEL Mist. 10 mg/m3 STEL Mist. 10 mg/m3 STEL Mist. 10 mg/m3 STEL Mist. 0 mg/m3 STEL Mist. 0 mg/m3 STEL Mist. 0 mg/m3 STEL Mist. 0 mg/m3 STEL Mist. 0 se only with a when general when general whe	5 mg/m3 TWA mist 10 mg/m3 STEL mist 5 mg/m3 TWA mist 2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction. 5 mg/m3 TWA Fume. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 5 mg/m3 TWA Mist. 500 ppm (2,000 mg/m3) TWA Mist. 0 mg/m3 STEL Mist. 500 ppm (2,000 mg/m3) TWA 10 mg/m3 STEL Mist. 500 ppm (2,000 mg/m3) TWA Semi-Solid when general ventilation is not sufficie below occupational exposure limits. If personal exposure cannot be controventilation, wear a properly fitted orgative by NIOSH. Observe OSHA regulation Safety glasses with side-shields. Gog Cover as much of the exposed skin a CAL AND CHEMICAL PROPERT Semi-Solid White Mild, Petroleum Not available Not available Not available Not available Not available Not available Not available Not available Not available Not available Not available Not available Not available Not available	5 mg/m3 TWA mist 10 mg/m3 STEL mist 5 mg/m3 TWA mist None 2 mg/m3 TWA Respirable fraction. 10 mg/m3 STEL Respirable fraction. 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. None 10 mg/m3 TWA Mist. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. None 5 mg/m3 TWA Mist. 500 ppm (2,000 mg/m3) TWA Mist. None 0 mg/m3 STEL Mist. 500 ppm (2,000 mg/m3) TWA None Use only with adequate ventilation. Local exhaust ventilation when general ventilation is not sufficient to control airborne below occupational exposure limits. None If personal exposure cannot be controlled below applicable ventilation, wear a properly fitted organic vapor/particulate by NIOSH. Observe OSHA regulations for respiratory use Safety glasses with side-shields. Goggles. Cover as much of the exposed skin area as possible with a cover as much of the exposed skin area as possible with a cover as much of the exposed skin area as possible with a cover as a properly fitted organic vapor/particulate by Nilos, Petroleum Not available Not available Not available Not available Semi-Solid White Nild, Petroleum Not available Not available Not available Se °F (20°C)) Not available Not available Not available Se °F (20°C) Not available Not available Not available Se °F (20°C) Not available Not available Se °F (20°C)

10.	STABI	LITY	AND	REA	/ΙΤΥ

Not determined Not available

28.9 %; 28.9 g/l

Negligible Not determined

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Oxides of sulfur. Oxides of carbon.
Incompatible materials:	Oxidizing agents.
Conditions to avoid:	None known

Autoignition temperature: Evaporation rate:

VOC content:

Solubility in water: Partition coefficient (n-octanol/water):

11. TOXICOLOGICAL INFORMATION

NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
No	No	No
	No No No	No No No No No No

Hazardous components	Health Effects/Target Organs	
Polyalphaolefins	No Target Organs	
Zinc oxide	Blood, Gastrointestinal, Immune system, Irritant, Kidney, Metabolic, Nervous System, Pancreas, Respiratory, Skin	
Calcium carbonate	Nuisance dust	
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Irritant	

12. ECOLOGICAL INFORMATION

Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Hazardous waste number:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

Not a RCRA hazardous waste.

of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12(b) Export Notification:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimus
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Zinc oxide (CAS# 1314-13-2).
California Proposition 65:	No California Proposition 65 listed chemicals are known to be present.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.
WHMIS hazard class:	Not controlled

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.