## **Material Safety Data Sheet**



Henkel

Revision Number: 002.1

**1. PRODUCT AND COMPANY IDENTIFICATION** 

Product name: Product type: Clover Silicon Carbide Grease Mix Sharpening compound

**Company address:** Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067 IDH number:233194Item number:39561Region:United StatesContact information:Telephone:860.571.5100MEDICALEMERGENCYPhone:Poison1-877-671-4608 (toll free)or 1-303-592-1711TRANSPORTEMERGENCYPhone:CHEMTREC1-800-424-9300 (toll free)or 1-703-527-3887Internet:www.henkelna.com

## 2. HAZARDS IDENTIFICATION

	EMERGE		
Physical state: Color: Odor:	Liquid, paste Gray Mild, Petroleum	HMIS: HEALTH: FLAMMABILITY: PHYSICAL HAZARD: Personal Protection:	1 1 0 See MSDS Section 8
CAUTION:	MAY CAUSE EYE	AND SKIN IRRITATION.	
Relevant routes of expos	sure: Skin, Inhalation, I	Eyes	
Inhalation: Skin contact Eye contact: Ingestion:	: May cause skin ir Contact with eyes	t or spray may cause irritation of the respira rritation with discomfort or rash. s will cause irritation. be harmful by ingestion.	tory tract and nasal passages.
Existing conditions aggr exposure:	avated by Eye, skin, and res	spiratory disorders.	
	This material is control to the terminal termin	considered hazardous by the OSHA Hazard	Communication Standard (29 CF

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 60
Mineral oil light naphthenic hydrotreat. <3% DMSO	64742-53-6	10 - 30
Silicon carbide	409-21-2	10 - 30
Silicon	7440-21-3	0.1 - 1
Cristobalite	14464-46-1	0.1 - 1

## 4. FIRST AID MEASURES

Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
Skin contact:	Wash with soap and water. If symptoms develop and persist, get medical attention.

Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms develop and persist, get medical attention.
Ingestion:	If conscious, drink plenty of water. Never give anything by mouth to an unconscious person. If symptoms develop and persist, get medical attention.
5. FIRE	FIGHTING MEASURES
Flash point:	> 93 °C (> 199.4 °F) HST-US D09F; Flash/Fire Point By Cleveland Open Cup
Autoignition temperature:	Not available
Flammable/Explosive limits - lower:	Not available
Flammable/Explosive limits - upper:	Not available
Extinguishing media:	Carbon dioxide, foam, powder
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In case of fire, keep containers cool with water spray.
Hazardous combustion products:	Oxides of carbon, oxides of nitrogen, irritating organic vapors.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed container for disposal.

## 7. HANDLING AND STORAGE

Handling:

Storage:

this product. Wash thoroughly after handling.

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist 5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) TWA 5 mg/m3 TWA Mist.	None	None
Mineral oil light naphthenic hydrotreat. <3% DMSO	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) TWA 5 mg/m3 TWA Mist.	None	None
Silicon carbide	10 mg/m3 TWA Inhalable fraction. 3 mg/m3 TWA Respirable fraction.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Silicon	None	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Cristobalite	0.025 mg/m3 TWA Respirable fraction.	1.2 MPPCF TWA Respirable. 0.05 mg/m3 TWA Respirable. 0.15 mg/m3 TWA Total dust.	None	None

Engineering controls:

**Respiratory protection:** 

Eye/face protection:

Skin protection:

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

Use NIOSH approved respirator if there is potential to exceed exposure  $\mathsf{limit}(s).$ 

Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Evaporation rate: Solubility in water: Partition coefficient (n-octanol/water): VOC content:

Liquid, paste Gray Mild, Petroleum Not available Not available Not available 285 - 900 °F (140.6 - 482.2 °C) None Not available 1.3548 Not available > 93 °C (> 199.4 °F) HST-US D09F; Flash/Fire Point By Cleveland Open Cup Not available Not available Not available Not available Not available Not available Essentially Zero

#### **10. STABILITY AND REACTIVITY**

Stability:

Stable

Hazardous reactions:

Not available

Hazardous decomposition products:

Incompatible materials:

Conditions to avoid:

Oxides of carbon. Hydrocarbons Acrid smoke and fumes.

Strong oxidizing agents.

Stable

# 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Mineral oil light naphthenic hydrotreat. <3% DMSO	No	No	No
Silicon carbide	No	No	No
Silicon	No	No	No
Cristobalite	Known carcinogen.	Group 1	No

Hazardous components	Health Effects/Target Organs
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant
Mineral oil light naphthenic hydrotreat. <3% DMSO	Irritant
Silicon carbide	Nuisance dust
Silicon	Irritant, Nuisance dust
Cristobalite	Carcinogen, Immune system, Kidney, Lung

## 12. ECOLOGICAL INFORMATION

Ecological information:

Do not empty into drains / surface water / ground water.

## **13. DISPOSAL CONSIDERATIONS**

#### Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Not a RCRA hazardous waste.

## **14. TRANSPORT INFORMATION**

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Water Transportation (IMO/IMDG)	
Proper shipping name:	Not regulated
Hazard class or division:	None

INOT regu
None
None
None

#### **15. REGULATORY INFORMATION**

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.	
TSCA 12(b) Export Notification:	None above reporting de minimus	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health None above reporting de minimus	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.	
WHMIS hazard class:	D.2.A, D.2.B	
16. OTHER INFORMATION		

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.