



Revision Number: 003.2 Issue date: 02/01/2010

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Pro Lock(TM) Tight(R) Anaerobic Gel

**Product type:** Anaerobic Adhesive

IDH number:234345Item number:51604Region:United States

Company address:Contact information:Henkel CorporationTelephone: 860.571.5100

One Henkel Way Emergency telephone: 860.571.5100

Rocky Hill, Connecticut 06067 Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:LiquidHEALTH:\*2Color:BlueFLAMMABILITY:2Odor:MildPHYSICAL HAZARD:1

Personal Protection: See MSDS Section 8

WARNING: COMBUSTIBLE LIQUID.

CAUSES EYE IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY CAUSE SKIN IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects** 

**Inhalation:** May cause irritation to nose and throat.

**Skin contact:** May cause allergic skin reaction. Causes skin irritation. **Eye contact:** Mild eye irritation. Contact with eyes will cause irritation.

**Ingestion:** May be harmful if swallowed.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	60 - 100
Dibutyl phthalate	84-74-2	10 - 30
Silicon dioxide	7631-86-9	5 - 10
Cellulose ester	9004-36-8	1 - 5
Saccharin	81-07-2	1 - 5
Cumene hydroperoxide	80-15-9	1 - 5
Propanediol-1,2	57-55-6	1 - 5
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1

IDH number: 234345 Product name: Pro Lock(TM) Tight(R) Anaerobic Gel

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Wash with soap and water. Remove contaminated clothing and footwear.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious

person. Keep individual calm. Get medical attention.

## 5. FIRE FIGHTING MEASURES

Flash point: 77.8 °C (172.04 °F) Pensky Martens closed cup

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not available

Flammable/Explosive limits - upper: Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Not available

Hazardous combustion products: Oxides of carbon. Irritating organic vapours.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Soak up with inert absorbent material (e.g. sand,

silica gel, acid binder, universal binder, sawdust). Store in a partly filled,

closed container until disposal.

## 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Do not breathe

gas/fumes/vapor/spray.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Store away from ignition sources.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Dibutyl phthalate	5 mg/m3 TWA	5 mg/m3 TWA	None	None
Silicon dioxide	6 mg/m3 TWA	20 MPPCF TWA 0.8 mg/m3 TWA	None	3 mg/m3 TWA Respirable fraction.
Cellulose ester	None	None	None	None
Saccharin	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA None (SKIN)	
Propanediol-1,2	None	None	10 mg/m3 TWA Aerosol.	None
1-Acetyl-2-phenylhydrazine	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

**Respiratory protection:** Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:BlueOdor:MildOdor threshold:Not availablepH:Not applicable

pH: Not applicable Vapor pressure:  $< 5 \text{ mm hg } (27 \,^{\circ}\text{C } (80.6 \,^{\circ}\text{F}))$  Boiling point/range:  $> 149 \,^{\circ}\text{C } (> 300.2 \,^{\circ}\text{F})$ 

Melting point/ range:

Specific gravity:

Vapor density:

Not available
1.1575
Not available

Flash point: 77.8 °C (172.04 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Not available

Not available

Not available

VOC content:

VOC 4 %

## 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

**Hazardous decomposition products:** Oxides of carbon. Irritating organic vapours.

Incompatible materials: Strong oxidizing agents. Strong reducing agents. Strong alkalis. Amines.

Other polymerization initiators.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

## 11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg (Estimated)

IDH number: 234345 Product name: Pro Lock(TM) Tight(R) Anaerobic Gel

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Dibutyl phthalate	No	No	No
Silicon dioxide	No	No	No
Cellulose ester	No	No	No
Saccharin	No	No	No
Cumene hydroperoxide	No	No	No
Propanediol-1,2	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No

Hazardous components	Health Effects/Target Organs		
Polyglycol dimethacrylate	Irritant, Allergen		
Dibutyl phthalate	Central nervous system, Developmental, Irritant, Reproductive		
Silicon dioxide	Nuisance dust		
Cellulose ester	No Target Organs		
Saccharin	No Target Organs		
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen		
Propanediol-1,2	Irritant		
1-Acetyl-2-phenylhydrazine	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity		

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

**U.S. Department of Transportation Ground (49 CFR)** 

Proper shipping name: Environmentally hazardous substances, liquid, n.o.s. (Di-n-butyl phthalate)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Marine pollutant: Di-n-butyl phthalate

**DOT Reportable quantity:**Dibutyl phthalate, alpha,alpha-Dimethylbenzylhydroperoxide

International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Di-n-butyl phthalate)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

IDH number: 234345

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Di-n-butyl

phthalate)

Hazard class or division: 9

Identification number:UN 3082Packing group:III

Marine pollutant: Di-n-butyl phthalate

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus Immediate Health, Delayed Health, Fire

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Dibutyl phthalate (CAS# 84-74-2). Cumene hydroperoxide (CAS# 80-15-9).

CERCLA Reportable quantity: Dibutyl phthalate (CAS# 84-74-2) 10 lbs. (4.54 kg)

Saccharin (CAS# 81-07-2) 100 lbs. (45.4 kg)

Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

WHMIS hazard class:

IDH number: 234345

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. B.3. D.2.B

#### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 14

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.